

Test Report

No.: SDHG1403003581FT

Date: Apr.28, 2014

Page 1 of 11

FOSHAN YUSHI FURNITURE CO. LTD
SHUINAN INDUSTRIAL AREA, SHATOU JIUJIANG TOWN,
NANHAI FOSHAN CITY, GUANGDONG, CHINA

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description : OFFICE CHAIR
Style / Item No. : YS-1605
Manufacturer : FOSHAN YUSHI FURNITURE CO. LTD
Supplier : FOSHAN YUSHI FURNITURE CO. LTD
Sample Receiving Date : Mar.25, 2014
Sample 1st Resubmission Date : Apr.18, 2014
Sample 2nd Resubmission Date : Apr.28, 2014
Test Performing Date : Mar.25, 2014 to Apr.28, 2014

Test Result Summary

Test(s) Requested	Result(s)
BS EN 1335-1-2000 (Type C)	See data on page 2~3.
BS EN 1335-2-2009 & BS EN 1335-3-2009+Corrigendum-2011	PASS (See Summary 1)

Summary:

1. Excluding the information for use.
2. For further details, please refer to the following page(s).

Signed for and on behalf of
SGS-CSTC Co., Ltd.

Bill Wang
Approved signatory



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

TESTS AND RESULTS
Part I. Test Conducted:

BS EN 1335-1:2000 Office furniture – office working chair – Part 1: dimensions –determination of dimensions

Basis of dimensions:

The dimensions in this standard are based on the conflicting requirements of anthropometric measurements, mechanical design, subjective preference and other factors. In general, they should be suitable for people between 1510 mm and 1920 mm in body height. People with body height outside this range may need furniture of different dimensions or a footrest. Due to the variation in population heights in different countries, there will be a variation in the percentage of the office population which the dimensions will accommodate in each country.

General Test Condition:

The following test program was conducted in a laboratory environment maintained at 15°C to 25°C and 50%±5 RH. The sample was individually tested after conditioning in the test environment for at least 24 hours prior to conducting the test.

The complete detailed procedures may be found in the referenced specification and are only summarized herein. Unless otherwise specified, the tests are carried out in the following order on the same sample.

No. of Sample:

1 piece (Sample 1). For more sample information and pictures, please refer to the following page.

Office Working Chair Type: Type C. For classification of type, please refer to Annex A.

Dimension Requirements							Test Results & Rating
Test Items	Adjustability	Type C					
		(-) Allow.	Min.	Max.	(+) Allow.		
SEAT							
Seat height	a	Adjustable Adjustable range	yes no	420 80	480 +	yes yes	452~532 mm
Seat depth	b	Non-adjustable Adjustable Adjustable range	no yes	380 400 +	+ + +	yes yes	490 mm
Depth of seat surface	c	/	no	380	+	yes	515 mm
Seat width	d	/	no	400	+	yes	500 mm
Inclination of seat surface	e	Non-adjustable Adjustable Adjustable range	no yes	-2 ° -2 ° +	-7 ° -7 ° +	no yes	-1.4 ° ~-18.4 °
BACK REST							
Height of the back supporting point "S" above	f	Non-adjustable Adjustable Adjustable range	no	170 + +	220 + +	no	215 mm
Height of the back pad -Adjustable	g	/		+	+		440 mm
-Non-Adjustable			no	260	+	yes	
Height of the upper edge the backrest above the seat surface	h	/	no	360	+	yes	495 mm
Backrest width	i	/	no	360	+	yes	465 mm

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

Dimension Requirements							Test Results & Rating
Test Items	Adjustability	Type C					
		(-) Allow.	Min.	Max.	(+) Allow.		
Horizontal radius of the backrest	k	/	no	400	+	yes	416 mm
Backrest inclination	l	Adjustable range		+	+		No requirement specified
ARM REST							
Length of armrest	n	/	no	200	+	yes	300 mm
Width of the armrest	o	/	no	40	+	yes	42 mm
Height of armrest above the seat	p	Non-adjustable Adjustable	no yes	200 200	250 250	no yes	240 mm
Distance from the front of the armrests to the front edge of the seat surface	q	/	no	100	+	yes	150 mm
Clear Width Between The Armrest	r	/	no	460	+	yes	495 mm
UNDERFRAME							
Maximum offset of the underframe (Anti-stumbling-dimension)	s	/	yes	+	x+50	no	380 mm (x+50=453)
Stability dimension	t	/	no	195	+	yes	230

Annex A: Classification of office work chair type

Type A, B and C are all required to have adjustable seat height and backrest inclination. They may also have any other adjustment features listed in Table A.1.

- **Type A.** In addition to the above, a type A chair is required adjustable seat depth, seat surface inclination, (at least 6°, and a height of backrest supporting point ("S") above the seat surface. The minimum seat height is required to be 400 mm with a minimum adjustment range of 120 mm.
- **Type B.** A type B chair has specified dimensions which are the same as those specified for a type A chair except that it is required to have a minimum seat height of 420 mm with a minimum adjustment range of 100 mm.
- **Type C.** A type C chair has specified dimensions which are similar to type A and B chairs except that limits to adjustment range and maximum dimensions are not frequently specified. The minimum seat height is 420 mm with a minimum adjustment range of 80 mm. This is to accommodate chairs with bulky upholstery.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

Part II. Test Conducted:

BS EN 1335-2:2009 Office furniture-office work chair - part 2: Safety requirements
 BS EN 1335-3-2009+Corrigendum-2011 Office furniture-office work chair - part 3: Test methods

Test Condition:

The following test program was conducted in a laboratory environment maintained at 15°C to 25°C and 50%±5 RH. The sample was individually tested after conditioning in the test environment for at least 24 hours prior to conducting the test.

The complete detailed procedures may be found in the referenced specification and are only summarized herein. Unless otherwise specified, the tests are carried out in the following order on the same sample.

No. of Sample:

1 piece (Sample 1). For more sample information and pictures, please refer to the following page.

Test	Test Description and Requirements	Test Results
EN 1335-2:2009, Clause 4 Safety requirements		
EN 1335-2:2009, Clause 4.1 General design requirements		
EN 1335-2:2009 Clause 4.1.1	<i>Corners and edges, trapping, pinching and shearing</i> All parts of the chair with which the user comes into contact during intended use, shall be so designed that physical injury and damage to property are avoided. These requirements are met when: a) the safety distance of accessible movable parts is either ≤ 8 mm or ≥ 25 mm in any position during movement; b) accessible corners are rounded with minimum 2 mm radius; c) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded with minimum 2 mm radius; d) the edges of handles are rounded with minimum 2 mm radius in the direction of the force applied; e) all other edges are free from burrs and rounded or chamfered; f) the ends of accessible hollow components are closed or capped.	PASS
EN 1335-2:2009 Clause 4.1.2	<i>Adjusting devices</i> Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall be possible to operate the adjusting device from sitting position in the chair.	PASS
EN 1335-2:2009 Clause 4.1.3	<i>Connections</i> It shall not be possible for any load bearing part of the chair to come loose unintentionally.	PASS
EN 1335-2:2009 Clause 4.1.4	<i>Avoidance of soiling</i> All parts which are lubricated to assist sliding (greasing, lubricating, etc.) shall be designed to protect users from lubricant stains when in normal use.	PASS

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

Test	Test Description and Requirements	Test Results
<p>EN 1335-2:2009 Clause 4.3</p>	<p>Stability during use The chair shall not overbalance under the following conditions: a) by pressing down on the front edge of the seat surface in the most adverse position; b) by leaning out over the arm rests; c) by leaning against the back rest; d) by sitting on the front edge. Requirement a) is fulfilled if the chair does not overbalance when tested according to 7.1.1 of EN 1335-3:2009 with the forces and numbers of cycles according to Table A.1 of this standard. Requirements b) and d) are fulfilled if the chair does not overbalance when tested according to 7.1.2, 7.1.3, 7.1.4 and 7.1.5 of EN 1335-3:2009 with the forces and numbers of cycles according to Table A.1 of this standard. Requirement c) is fulfilled if the chair does not overbalance when tested according to 7.1.6 or 7.1.7 of EN 1335-3:2009 with the forces and numbers of cycles according to Table A.1 of this standard.</p>	<p>PASS (For more test details, please refer to the following pages)</p>
<p>EN 1335-2:2009 Clause 4.4</p>	<p>Rolling resistance of the unloaded chair The unloaded chair shall not roll unintentionally. This requirement is met when: a) the castors are of identical construction; b) the rolling resistance is ≥ 12 N when tested according to EN 1335-3:2009, 7.4.</p>	<p>PASS (For more test details, please refer to the following pages)</p>
<p>EN 1335-2:2009 Clause 4.5</p>	<p>Strength and durability The chair shall be constructed to ensure that it does not create a risk of injury to the user of the chair under the following conditions: a) sitting on the seat, both centrally and off-centre; b) moving forward, backwards, and sideways while sitting in the chair; c) leaning over the arm rests; d) pressing down on the arm rests while getting up from the chair. These requirements are fulfilled when after the tests specified in 7.2.1, 7.2.2, 7.2.6, 7.3.1 and 7.3.2 of EN 1335-3:2009 with the forces and numbers of cycles according to Table A.2 of this standard: e) there are no fractures of any member, joint or component, and f) there is no loosening of joints intended to be rigid, and g) no major structural element is significantly deformed and the chair fulfils its functions after removal of the test loads. h) after the test in 7.2.3 of EN 1335-3:2009 with the forces and numbers of cycles according to Table A.2 of this standard, the arm rests show no fracture.</p>	<p>PASS (For more test details, please refer to the following pages)</p>

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

Test	Test Description and Requirements	Test Results
EN 1335-3:2009 Clause 7.2.6	Foot rest static load test Apply a vertical force 1300N acting 80 mm from front edge of the load bearing structure of the foot rest at those points most likely to cause failure. For round cross section ring shaped footrests, the force shall be applied through the centre of the ring cross section. If the chair tends to overturn load the seat to prevent overturning and report this. Number of cycles: 10 cycles	/ Not applicable
EN 1335-3:2009 Clause 7.3.2	Arm rest durability Apply simultaneously and cyclically the force 400N on each arm rest at points 100 mm behind the foremost point of the arm rest length. Apply a force of (10 ± 5) N through a loading device in principle functioning as shown in Figure 4. With this force applied adjust the apparatus so that each "arm" of the test apparatus has an angle of 10° ± 1° to the vertical. The length of the "arm" of the test apparatus shall be 600 mm ± 10 mm. The arm rests shall be allowed to deform freely. Number of cycles: 60000 cycles	PASS
EN 1335-3:2009 Clause 7.2.3	Arm rest downward static load test – central The arm rests shall be loaded vertically by means of the local loading pads. The loading points shall be at the mid point of the arm rest length and centred side to side. Apply the force 750N to both arm rests simultaneously for 5 cycles.	PASS
EN 1335-3:2009 Clause 7.1.1	Front edge overturning Do not position the chair with the stops against the supporting points. Fix the strap to the chair, i.e. the force is applied at the point on the front edge that is furthest from the axis of rotation, and allows the mass 27kg to hang freely.	PASS
EN 1335-3:2009 Clause 7.1.2	Forwards overturning Position the chair with two adjacent supporting points on the front against the stops. Apply by means of the stability loading device a vertical force 600N acting 60 mm from the front edge of the load bearing structure of the seat at those points most likely to result in overturning. Apply for at least 5 s a horizontal outwards force 20N from the point on the seat surface where the vertical force is applied.	PASS
EN 1335-3:2009 Clause 7.1.3	Forwards overturning for chairs with footrest For chairs with footrests repeat the principle of 7.1.2 on the footrest. For round cross section ring shaped footrests, the vertical force 1 100N shall be applied through the centre of the ring cross section.	/ Not applicable
EN 1335-3:2009 Clause 7.1.4	Sideways overturning for chairs without arm rests Position the chair with two adjacent supporting points on one side against the stops. Apply by means of the stability loading device a vertical force 600N acting 60 mm from the side edge of the load bearing structure of the seat at those points most likely to result in overturning. Apply for at least 5 s a horizontal sideways force 20N outwards from the point on the seat surface where the vertical force is applied.	/ Not applicable

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

SGS CSTI Standards Technical Services (Shenzhen) Co., Ltd. | 1F, 1st Building, European Industrial Park, No. 1 Shunhe Road, Wusha Section, Daikang Town, Shunde, Foshan, Guangdong, China | 528333 t (86-757)22805888 f (86-757)22805858 www.sgs.com.cn
 Guangzhou Branch: Guangzhou City, China | 中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805858 e sgs.china@sgs.com

Test	Test Description and Requirements	Test Results
EN 1335-3:2009 Clause 7.1.5	Sideways overturning for chairs with arm rests Position the chair with two adjacent supporting points on one side against the stops. Apply by means of the stability loading device a vertical force 250N acting at a point 100 mm from the fore and aft centre line of the seat at the side where the supporting points are restrained and between 175 mm and 250 mm forward of the rear edge of the seat. Apply a vertical downward force 350N acting at points on the arm rest which is on the same side as the restrained supporting points up to a maximum 40 mm inwards from the outer edge of the upper surface of the arm rest, but not beyond the centre of the arm rest, and at the most adverse position along its length. Apply a horizontal sideways force 20N outwards from the same point for at least 5 s.	PASS
EN 1335-3:2009 Clause 7.1.6	Rearwards overturning for chairs without back rest inclination Position the chair with two adjacent supporting points on the back against the stops. When an independent lumbar adjustment is fitted it shall be set in the most adverse configuration. A vertical force 600N shall be applied at point "A" and a horizontal force 192N shall be applied at point "B". If the back rest pad is pivoting around a horizontal axis above the height of the seat and is free to move, the horizontal force shall be applied on the axis. If height adjustable, the axis shall be set as close as possible to 300 mm above point "A".	PASS
EN 1335-3:2009 Clause 7.1.7	Rearwards overturning for chairs with adjustable back rest inclination Do not position the chair with the supporting points against the stops. When an independent lumbar adjustment is fitted it shall be set in the most adverse configuration. Load the chair with 13 discs so that the discs are firmly settled against the back rest. If the height of the stack of discs exceeds the height of the back rest, prevent the upper discs from sliding off by the use of a light support.	PASS
EN 1335-3:2009 Clause 7.2.3	Arm rest downward static load test – central The arm rests shall be loaded vertically by means of the local loading pads. The loading points shall be at the mid point of the arm rest length and centred side to side. Apply the force 900N to both arm rests simultaneously for 5 cycles.	PASS
EN 1335-3:2009 Clause 7.4	Rolling resistance of the unloaded chair The chair shall be placed on the test surface and shall be pushed or pulled over a distance of at least 550 mm. A speed of (50 ± 5) mm/s shall be maintained over the measuring distance. The force shall be applied at a height of (200 ± 50) mm above the test surface. Record the force used to push or to pull the chair over the distance from 250 mm to 500 mm as the rolling resistance. The Rolling resistance shall be ≥12N.	PASS
Additional Function Tests: No loss of serviceability after tested.		
EN 1335-3:2009 Clause 7.2.4	Arm rest downward static load test – front The arm rests shall be loaded vertically by means of the local loading pads. The loading points shall be 75 mm from the front edge and centred side to side. Apply the force 450N to both arm rests simultaneously. Number of cycles: 5 cycles.	PASS

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com

SGS CSTI Standards Technical Services Co., Ltd. 1F, 1st Building, European Industrial Park, No. 1 Shunhe Road, Wusha Section, Daikang Town, Shunde, Foshan, Guangdong, China 528333 t (86-757)22805888 f (86-757)22805858 www.sgs.com.cn
 Guangzhou Branch: Guangzhou Customs Special Inspection Laboratory 中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805858 e sgs.china@sgs.com

Test	Test Description and Requirements	Test Results
EN 1335-3:2009 Clause 7.2.5	Arm rest sideways static load test Apply an outward horizontal force 400N to both arm rests simultaneously. Apply the forces to the edge of the arm rest at the point along the arm rest most likely to cause failure but not less than 75 mm from the front or rear edge. Number of cycles: 10 cycles.	PASS
EN 1335-3:2009 Clause 7.3.3	Swivel test The base of the chair shall be secured on a rotating table with a test surface so that the rotating axis of the chair coincides with the rotating axis of the table. The upper part of the chair shall be loosely fixed in such a way as not to hinder the rotation of the base. Load the seat in loading point A with a mass 60kg and in loading point C with a mass 35kg or any equivalent loading which will result in the same downwards force and bending moment on the chair. The angle of rotation shall be 360° at a rate of (10 ± 5) cycles/minute. Change direction after each rotation. Number of cycles: 120000 cycles	PASS
EN 1335-3:2009 Clause 7.3.4	Foot rest durability Using the local loading pad apply a vertical downward force 900N to the foot rest at the point most likely to cause failure but not less than 80 mm from the front edge. For round cross section ring shaped foot rests, the force shall be applied through the centre of the ring cross section. Number of cycles: 50000 cycles	/ Not applicable
EN 1335-3:2009 Clause 7.3.5	Castor and chair base durability This test does not apply to chairs with castors which are braked when the chair is loaded. The chair shall be placed on a rotating table with a test surface so that the rotating axis of the chair coincides with the rotating axis of the table. Load the seat in point A with 110kg. The base shall be loosely fixed in such a way that there is no rotation of the base but that the natural movements of the castors during testing are not prevented. The castors shall be left free to swivel, the table shall be rotated with a rate of 6 cycles per minute. The angle of rotation shall be from 0° to 180° and back. One rotation forward and one rotation backward constitutes one cycle. Alternatively attach the chair to a device that provides a linear movement of (1 000 ± 250) mm and a test surface. Load the seat in point "A" with M1. The base shall be loosely fixed in such a way that there is no rotation of the base but that the natural movements of the castors during testing are not prevented. The castors shall be left free to swivel, the device shall move with a rate of 6 cycles per minute. One movement forward and one movement backward constitutes one cycle. Number of cycles: 36000 cycles	PASS

Remark:

1. For the sample information and pictures, please refer to the following page.

SAMPLE INFORMATION AND PICTURES

Weight: 16.00 kg

Overall Dimensions: 605 mm L x 600 mm W x 940~1020 mm H

Other Dimensions: Base radius 345mm, base weight 2.15 kg.

Sample as Received



View 1



View 2



View 3




View 4

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained therein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com



View 5



View 6



View 7



View 8

End of Report

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client, and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To ensure the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN.Doccheck@sgs.com